

Hyattsville Volunteer Fire Department  
6200 Belcrest Rd  
Hyattsville, MD 20782

January 24, 2024

Atlantic Emergency Solutions, the Maryland dealer for Wheeled Coach Ambulance, is pleased to present you with a price for (1) Wheeled Coach 1170F, Ambulance\*

The price to customize and manufacture the ambulance matching your specifications is as follows:

**Total cost per unit \$ 387,522.00\***

The price includes the following:

Factory Pickup and Transportation

Atlantic will drive new unit from Wheeled Coach to the Baltimore Service facility after final inspection

Dealer Pre-Delivery Inspection

Atlantic service center will perform a pre-delivery inspection after delivery from the factory

Fuel and Tags

Atlantic will provide new unit with a full tank of fuel and a temporary tag

Applied Discount

A pre-payment discount is reflected in the above per unit proposal cost. Payment must be made within 30 days of contract signing and invoice receipt

\*Proposal price is based on today's 2024 OEM chassis model year pricing. Atlantic Emergency Solutions nor the ambulance manufacturers have regulatory control over the OEM chassis builder pricing or their scheduling and as such Atlantic Emergency Solutions reserves the right to modify the final amount due based on chassis model and cost changes. Customer shall be notified immediately of any chassis cost changes.



## Proposal for Furnishing Ambulance

January 24, 2024

Hyattsville Volunteer Fire Department  
6200 Belcrest Rd  
Hyattsville, MD 20782

Upon an order being placed by you, and final acceptance by Wheeled Coach the ambulance and equipment herein named will be manufactured for the following prices:

**(1)– Wheeled Coach Ambulance                      Total Cost \$ 387,522.00**

Said ambulance and equipment are to be built and shipped in accordance with the specifications hereto attached, delays due to strikes, war, or intentional conflict, failures to obtain chassis, materials, or other causes beyond our control not preventing, within 28-30 months from the receipt of order and the acceptance thereof by Wheeled Coach.

**Taxes:** Tax is not included in this proposal. In the event that the purchasing organization is not exempt from sales tax or any other applicable taxes and/or the proposed ambulance does not qualify for exempt status, it is the duty of the purchasing organization to pay any and all taxes due.

**Cancellation:** In the event this proposal is accepted, and a purchase order is issued then cancelled or terminated by Customer before completion, Atlantic Emergency Solutions may charge a cancellation fee of 30% of the purchase price.

**Terms:** The terms of this proposal will be governed by the laws of the state of Virginia. No additional terms or conditions will be binding upon Atlantic Emergency Solutions unless agreed to in writing and signed by a duly authorized officer of Atlantic Emergency Solutions

This proposal is valid for 30 days from date of proposal

Brian Griffin  
Regional Account Manager  
Atlantic Emergency Solutions  
7462 Candlewood Rd  
Hanover, MD 20176  
443.417.6968  
bgriffin@atlanticemergency.com

Since the beginning in 1973, Wheeled Coach has kept its eye on the future; always working with customers to improve upon today's ambulances and rescue vehicles. The goal has been to make emergency vehicles safer for both patient and crew, and at the same time, make them more efficient.

Located in Winter Park, Florida, Wheeled Coach offers a diverse product line, allowing for unique and custom ambulance configurations. Being an ISO 9001 certified ambulance manufacturer, Wheeled Coach prides itself on safety, innovation and maintenance.

At Atlantic Emergency Solutions we have built an internal and external infrastructure capable of meeting the diverse needs of our customers. With twelve (12) Service Centers, one (1) Collision and Paint Center, over one hundred (100+) Service Technicians and over fifteen (15) fully stocked Service Vehicles located throughout Delaware, Maryland, North Carolina, Pennsylvania, South Carolina, Virginia and West Virginia, our service is unmatched. It is our mission to not only make the duration of your emergency vehicle a pleasant experience, but to assist in any way possible.

Atlantic Emergency Solutions has invested heavily in providing warranty, routine and emergency service to its customers in Maryland. Atlantic Emergency Solutions views the acquisition of custom ambulances by one of our customers not merely a purchase but an investment. This investment needs to be protected with best in local service! Should you have any additional questions regarding any information in this proposal, please do not hesitate to call or email at the below contact information.

I look forward to the opportunity of continuing the working relationship with the members of the Hyattsville Volunteer Fire Department and all those involved in the fire and emergency field.





## QUOTATION

Hyattsville Volunteer Fire Department  
6200 Belcrest Rd  
Hyattsville, MD 20782

Atlantic Emergency Solutions  
Brian Griffin  
7462 Candlewood Rd  
Hanover, MD 21076  
bgriffin@atlanticemergency.com

Exp. Date: 02/22/2024

Quote No: 10537-0005

01/22/2024

Page 1

ID	S	PART NO	DESCRIPTION	QTY
REV		== WC-Wheeled Coach Boilerplate - 1.074 07/28/23 ==		
REV		ORDER COORDINATOR		
REV		00-00-0015	Order Coordinator - Factory to assign	1
REV		INFORMATION		
REV		00-01-4005	State Contract	1
REV		00-01-4117	Manufacturer Certified ISO 9001	1
REV		WARRANTY		
REV		00-02-8710	WC, Warranty, Conversion, 12 Month	1
REV		00-02-8720	WC, Warranty, Paint, 60 month Prorated, Standard	1
REV		00-02-8730	WC, Warranty, Structural, 20 Years, Std., Mods	1
REV		00-02-8740	WC, Warranty, Limited Electrical	1
REV		00-02-8750	WC, Warranty, Cabinet Construction	1
REV		== WC-Type 1 170 Module - 1.074 07/28/23 ==		
REV		00-00-0247	***** OUTSIDE GRAPHICS- 24/7 *****	1
REV		CERTIFICATIONS REQUIRED		
REV		00-05-0050	This unit built in accordance with KKK-A-1822-F in effect on the date of order with exceptions as noted herein.	1
REV		00-05-0150	Customer opts out of KKK-1822F CN 10 Requirements	1
			SPECIAL NOTE:	
			The cabinet doors and hardware you have selected for this order does not meet the performance requirements of the SAE J3058 Ambulance Interior Storage Compartment Integrity	
			Section 3.11.3 of KKK-A-1822F as revised July 1,2017 specifically relates to Storage compartments and Cabinet Design.	
			1) All interior enclosed stowage devices shall be tested to their rated weight capacity in accordance with the requirements of SAE J3058.	
			2) Stowage devices shall not come open in transit.	
			3) Storage for the main oxygen cylinder shall be accessible for replacement from an outside position.	
			4) The oxygen compartment shall be provided with at least a 9 sq. in. of open vent to dissipate/vent leaking oxygen to the outside of the ambulance.	
			5) Oxygen cylinder compartment shall not be utilized for storage of any other	

ID	S	PART NO	DESCRIPTION	QTY
			equipment.	
			6) All interior enclosed stowage devices shall be labeled with their rated weight capacity.	
<b>REV</b>			<b>01- CHASSIS REQUIREMENTS</b>	
	U	01-00-00SR	Nederman Exhaust System w/ Electromagnetic Connection REF SR # 2230168F, Line 13. NOTE: Critical Measurement: 24" from center of magnet to center of tailpipe. CUSTOMER WILL NOT ACCEPT IF MEASUREMENT IS NOT CORRECT. Each unit may be different depending on exact location of tailpipe. Mounted magnet on compt 2 , photo on file from previous units.	1
	U	01-00-01SR	Mounting Bracket Behind Driver's Seat SR REF # 2230168F Line 22. (SO-BRKT1-351192) Ref previous # 554849. Install mounting brackets as required for ALPHA sirens.	1
	U	01-00-02SR	Mounting Bracket Behind Passenger Seat SR REF # 2230168F Line 21 (SO-BRKT1-351192) Ref previous # 554849. Install mounting bracket for customer's radio behind front passenger seat.	1
	U	01-00-03SR	Intermotive AutoGuard System	1
	U	01-00-04SR	HAAS Automotive System SR#2230507F	1
			HAAS Alerting System with 5 year subscription Responder-to-Vehicle (R2V) Safety Cloud (HA-7)	
<b>REV</b>			<b>FORD CHASSIS</b>	
	U	01-01-26SR	WC, 2024 Ford F550, XLT 4X4, 193" W/B, 19,500 GVWR (Special Order) Estimated Auto throttle OEM Ford Dual Alternators OEM Ford Mirrors, OEM, Heated/Remote Cab seats OEM 40/20/40 split bench (Center removed) New for 2020- Sync 3 Enhanced voice recognition communication and entertainment system 8" LCD Capacitive Touch screen in center stack w/swipe Capability Pinch to Zoom capability AppLink 911 assist Apple carPlay and Android Auto Smart-charging USB-C Ports (2)	1

ID	S	PART NO	DESCRIPTION	QTY
			NOTE: Due to changes made to the OEM chassis by the manufacturer -some options may have to be changed to fit the new configuration.	
	U	01-01-27SR	Maximum Speed Limit SR#2230393	1
			The chassis speed shall be programmed to a maximum of 75 MPH	
REV		01-02-0100	Domestic Chassis	1
REV			<b>ALTERNATORS</b>	
REV		01-03-1001	Alternator - Standard OEM	1
REV			<b>SUSPENSION</b>	
REV		01-07-7618	MD, Rear Suspension, Liquid Spring- 2017+ F550, 19.5k GVWR, 4x4 Dump Feature activated by the Left rear access door. Override switch to be on right rear entry door Ignition switch Hot, Standard.	1
			Per KKK, the rear suspension shall only lower the module when the vehicle is in park and the parking brake is set.	
REV			<b>HIGH IDLE</b>	
REV		01-13-1530	MD, Intermotive Module controllers, F series, Diesel ,2023+	1
REV		01-13-1675	High Idle Controls, OEM	1
REV			<b>FRONT END ALIGNMENT</b>	
REV		01-17-7501	Front End Alignment, None- QC Check -Standard	1
REV			<b>OUTSIDE REAR VIEW MIRRORS</b>	
REV		01-20-0104	Mirrors, OEM-STD	1
REV			<b>CAB INTERIOR OPTIONS</b>	
REV		01-21-4455	MD, Cab Seats, Re-upholster, Gunmetal Gray, Outside Vendor by outside Vendor	1
REV			<b>WHEEL COVERS</b>	
REV		01-24-2022	MD, Wheel Covers, Delete Set of Four (4)	1
	U	01-24-21SR	Turn Rear Wheel Outboard Valve Stems & Install (2) Valve Extenders REF SR #2230168F, Line 29.	1
REV			<b>BASE CONVERSION</b>	
REV		01-45-0226	MD, Conversion, Type 1, 170 Module, F550 4x4 - 23-1	1
REV			<b>MODULE BODIES:</b>	
REV		02-01-2122	MD, Interior Headroom, 72 Inches	1
REV		02-01-3124	MD, Module, Type 1, 170" Body Length, Duraseam Doors, 170" L x 95" W	1
REV		02-01-3154	MD, Body Width 96" Skin to Skin	1
REV		02-01-9564	MD, Aisle Space, 50", Type 1 DELETE THIS LINE REFERENCE 02-01-95SR	1

ID	S	PART NO	DESCRIPTION	QTY
	U	02-01-95SR	Aisle Space Type I Custom (10153520) Aisle width in area to rear of RF cabt is 48", ilos. Depth of compts "6", "4", "2", & "1" are reduced. Add black grip tape to top of curbside entry door stainless sill plate.(see picture on file) and bottom step. Note: stainless steel wheelwell covers are not required. C/S and rear stainless steel thresholds to be screwed down with counter sunk screws. Door handle on compts "1" to be level with door handle on compt "4". Center the rear vent on drivers side between the M9 lights	1
REV		02-02-1301	MD, All Module Skins, 0.125 inch	1
REV			<b>03 - MODULE EXTERIOR</b>	
REV		03-01-1501	MD, Type 1, General Body Construction Spec	1
REV		03-01-1503	MD, Type 1, Vehicle Body Structure Spec	1
REV			<b>UNDERCOATING</b>	
REV		03-02-0230	MD, Undercoating, Dolphin, Type 1,9 & 3, 160" and over module Installed by 24-7 Graphics.	1
REV			<b>EXTERIOR MODULE CONSTRUCTION</b>	
REV		03-03-1055	MD, Corner Post Guard, Diamond Plate, Full Height, (4)	1
REV			<b>DROP SKIRTS</b>	
REV		03-03-2513	MD, Drop Skirt both sides, 6" forward of rear wheels Note: Bright finish fender flares will not work, must use rubber	1
	U	03-03-26SR	Custom Body Per Previous Units Ref SR # 2230168F, line 20.	1
REV			<b>FUEL FILLS &amp; SPLASH PLATE</b>	
REV		03-03-8030	MD, Housing Fuel Fill, Cast Aluminum, Type 1	1
REV		03-03-8335	MD, Fuel Fill Splash Plate, Stainless, 10in Wide - installed below fuel fill full perimeter to bottom of skirt rail to protect body- attach to body using double sided tape - no screws	1
REV			<b>DEF FILL HOUSING AND SPLASH PLATE</b>	
REV		03-03-8615	MD, DEF Fill, Housing, For Ford F series	1
REV			<b>REAR KICKPLATE</b>	
REV		03-03-9066	WC, Rear Kick plate,Under-Ride Bumper, w/ Tag recess, No lights	1
REV			<b>SUB-FLOOR SYSTEM</b>	
REV		03-04-0164	MD, Floor, Interior, Non Wood, Expanded PVC, Type 1	1
REV			<b>MODULE ENTRANCE</b>	
REV		03-05-0250	MD, Module Access, CS Door Relocated Forward "Must use 5x10 sheet to eliminate seams in Bulkhead"	1
REV			<b>MODULE DOORS, HANDLES &amp; HOLD OPENS</b>	

ID	S	PART NO	DESCRIPTION	QTY
REV		03-06-0115	WC, Duraseam Hinged Doors with Hidden Jambs - Magnetic door switches, Standard	1
REV		03-06-0710	MD, Hold Open Rear Entry Doors, (4) 3" Cast Grabber for rear access doors,. Eng/Production: thru-bolt with nyloc nuts all parts of hold-opens thru flatbar reinforcement welded into module and rear entry doors !!!!!!!	1
REV		03-06-0817	MD, Hold Open - Gas Strut, Curb Side Entry Door, 35# New Code Per ECN 1823 Note: Customer has had strut brackets loosen on previous units. Provide a aluminum brace inside door jam per Eng design, for a secure assembly.	1
REV		03-06-0820	WC, Strap, 2" wide Black, Retaining for CS access door To prevent the door from opening past 90 degrees.  (2) 2" Nylon strap that limits the curbside door travel beyond the struts limits.  Upper strap 1/3 from top of door, lower 1/3 from bottom of door.	2
REV		03-06-1052	WC, Entry Door Handles, Trimark, Chrome/Black (interior relocated to Top) With Push button Emergency Release top and bottom of each door. Includes exterior Latches on all three entry doors.	1
REV		03-06-4202	MD, Electrical to Required Doors, Curly Cord w/Compression fitting (Per Door)	1
REV		03-06-4333	MD, Door Reflector, 3 In, Red, Screw-On, Each Install 3" round reflectors, (1) on each module entry door, lower outboard corner	3
REV		03-06-5002	MD, Entry Door LED Warning Lights, Red Whelen OS Series, Each Installed as follows: (1) CS entry door, interior door panel approx 55" from bottom of door, (1) on each rear entry door, approx. the same height as the brake lights on rear of module door.- lights are to flash whenever teach specific door is open, ign. hot.. Add magnetic switch to left entry door .	3
	U	03-06-51SR	MD, Compartment Door LED Warning Lights, Red Whelen OS Series Ref SR # 2230168F line27.. Each SAP # 10185812.	1



ID	S	PART NO	DESCRIPTION	QTY
			(1) on compt "8", interior door panel, approx 40" from bottom of compt door.	
			(1) on compt "6", interior door panel, approx 55" from bottom of compt door	
			(1) on compt "4" leading door, interior door panel, approx 55" from bottom of compt door	
			(1) on compt "2" leading door, interior door panel, approx approx 30" from bottom of door	
			(1) on compt "1", interior door panel, approx 55" from bottom of compt door	
			To activate only when each specific door is open, ign hot.	
			No lights on compt "4" trailing door.	
REV		03-06-6126	MD, Power Door Locks, Electric, Trimark Paddle, Each Entry Door Includes actuator, actuator connector, actuator pigtail, relay connector -	2
REV		03-06-6127	MD, Power Lock, Electric, Trimark Paddle, Each Compartment Door. Includes actuator, actuator connector, actuator pigtail, relay connector - same switch as entry doors	6 Use
REV		03-06-6130	MD, Switch, Momentary Rocker, Activate Power Door Locks (1) installed in C/S action area switch panel (1) installed recessed on backboard wall near rear entry doors with timer and override switches.	2
REV		03-06-6137	MD, Relay Control Circuit, Power Door Locks	1
U		03-06-61SR	Switch, Stealth, Cab/Body Doors, with red Cover, ILOS REF SR # 2230168F, Line 8. (SO-SW-351192) w/ red cover.  streetside rear of truck underneath an inlet cover, mounted above tail light assembly.  Small (w/4 screws) painted plate centered on left rear below the M9 lights to house the stealth switch under the auto eject red cover.	1
REV			<b>ENTRY DOOR INNER PANELS</b>	
REV		03-06-7232	MD, Entry Panels, Durasafe, Stainless Steel, w/ Center Chevrons, (pick color) - Durasafe Design - Aluminum Center Panels covered: reflective tape COLORS:	1

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>SIDE DOOR STEP</b>	
REV		03-08-2112	MD, Side Entry Step Well, Type I, Aluminum Diamond Plate	1
REV		03-08-2157	MD, Double Step Well w/ floating middle step the step well will be deepened 3" and the bottom step will be full depth and upper step will be a 9" floating step	1
REV		03-08-3056	MD, Light, Side Entry Step well, LED, Whelen #TOCACCCR, 2"	1
REV			<b>WINDOWS</b>	
REV		03-09-4109	MD, Window, Upper, CS/Slider, Rr/Fixed, Privacy Tint, PAN	1
REV			<b>MODULE TO CHASSIS MOUNTING SYSTEM</b>	
REV		03-10-1212	MD, Module to chassis mounting system, Type 1 Ford Long WB	1
REV			<b>CAB TO MODULE</b>	
REV		03-11-2502	MD, Bellows, Pass thru, Unigrip, F1 2008+,  With Aluminum cab insert.	1
REV			<b>REAR BUMPER AND REAR STEP CONSTRUCTION</b>	
REV		03-12-2503	MD, Rear Bumper w/ Skids & Flip Up, F1/C1, w/LED DOT lights  w/ Gator Grip on flip up step. Lights in side of bumper pod Steady burn with lights on	1
REV		03-12-2550	MD, Coating, Polyurethane, Rear Bumper Supports Black	1
REV		03-12-2552	MD, Rear Bumper, Pontoon Reinforcement	1
	U	03-12-25SR	Dock Bumpers, Black, On Rear Ref SR # 2230168F line 28. Same as previous 554849.	1
	U	03-12-26SR	Bumpers For Rear Flip Up Step REF SR # 2230168F, line 15. Per Eng transmittal.  See ref pic on server with SR same as customer's last units 554849, rubber skirt rail material.	1
REV			<b>INSULATION</b>	
REV		03-13-3006	MD, Insulation, Walls and Ceiling, R11 Fiberglass Batt	1
REV		03-13-3020	MD, Insulation, Spray Foam w/ undercoating, under floor ATTENTION :: The UNDER CARRIAGE is to be FOAMED to insulate the floor. The spray foam under the module shall be protected by rubberized undercoating. This shall be done at 24/7  NOTE: NO SPRAY FOAM IN THE WHEEL WELL AREA. THIS IS TO BE DOLPHIN UNDERCOATING SPRAY ONLY	1

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>RUB RAIL AND FENDER RINGS</b>	
REV		03-15-8350	MD, Fender Flare, Black Rubber	1
	U	03-15-SR01	Hard Black Plastic Rub Rails ILOS	1
			SR # 2230168F, line 3. (10815028)	
			Black rub rails to match Pierce rub rails. Includes rubber fenderette	
REV			<b>SPLASH GUARDS AND RUNNING BOARDS</b>	
REV		03-16-1722	MD, Mud Flaps, Rear, Non Logo	1
REV		03-16-3605	MD, Running Boards, F450/550 w/Gator Grip	1
REV			<b>DRIP RAILS</b>	
REV		03-17-1020	MD, Drip Rail Trim Moldings Over Door Openings	1
REV			<b>CAB TO PATIENT AREA ACCESS</b>	
REV		03-19-2301	MD, Bulkhead, Unigrip, Type 1F/D, Pass Thru, w/ Sliding Lexan Window	1
	U	03-19-23SR	MD Bulkhead, Custom	1
			REF SR # 2230168F, line 22 (10201501) ref previous unit # 554849.	
REV			<b>LICENSE PLATE HOLDER</b>	
REV		03-20-4053	WC, License Plate Holder, Cast LP0002-1 for Under ride Bumper in rear kick plate, centered	1
			License holder comes with (2) LED lights.	
REV			<b>EXTERIOR COMPARTMENT CONSTRUCTION</b>	
REV		04-01-0504	MD, Exterior Compartment, Sweep out, Each	5
			All compartments to be sweep out	
REV		04-01-3017	MD, Door Sill Protector, Stainless, All Comps	1
			Door Sill Protection - Install Stainless Steel sill protector on lower edge of all door frames to prevent paint damage	
REV		04-01-5106	MD, Polyurethane Coating per compartment	5
			light gray	
REV		04-01-5112	MD, Exterior Compartment, Upgrade to .125 Aluminum, All compartments	5
			Machine stamped louvers located above the floor line for venting.	
	U	04-01-51SR	Coating, Polyurethane Compt Shelves ILOS	1
			REF SR # 2230168F Line 26.	
			Black polyurethane, for all exterior comp shelves and dividers ILOS.	
REV			<b>EXTERIOR COMPARTMENT DOORS</b>	
REV		04-02-0514	WC, Compartment Door Latch, Edge Paddle, Trimark, Trailing Door	2
			Interior edge style handle comps "#2" & "#4"	

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>COMPARTMENT PADDLE HANDLES</b>	
REV		04-02-0602	MD, Compartment Handle, Trimark Chrome/Black, Locking Paddle, Curbside Compartment #6	1
REV		04-02-0604	MD, Compartment Handle, Trimark Chrome/Black, Locking Paddle, Street side Compartments 1, 2 Leading door, 4 leading door Compartment 8, reversed hinge	4
REV			<b>COMPARTMENT DOOR HOLD OPEN</b>	
REV		04-02-7753	MD, Hold Open Gas Strut, Ext Comp, 30lb Compartments 1, 2 (leading door)	2
REV		04-02-7755	MD, Hold Open, Gas Strut, Comp Door Only, 110 Degree, 30lb Compartments 2 (trailing door only), Compartment 6, & Compartment 4 (both doors)	4
REV		04-02-7757	MD, Hold Open, Gas Strut, RF Comp, 30lb	1
REV		04-02-7763	MD, Hold Open, Cast, Grabber (1), 3" RF compt "8" door, even with rear intersection light, approx the same distance from hinge as hold opens on rear entry doors. Eng/Production: thru-bolt with nyloc nuts all parts of hold-opens thru flatbar reinforcement welded into module and compt "A" door !!!!!!!	1
REV			<b>COMPARTMENT LIGHTING</b>	
REV		04-03-1486	MD, Compartment Lighting, LED Solico Reel lights, 160+ Module (new code)  both vertical edges near door jambs and across top edge near door jamb, compartments "1", "2", "4", "6", "6.5", & "8". Standard 3" Round O2 light	1
REV			<b>COMPARTMENT #1 - STREETSIDE FWD</b>	
REV	XS	04-06-0452	MD, Compartment #1, Custom (Special Request) Match previous unit #554849.  Full sweepout. Move O2 vent up beside warning light or lower to make space for graphics.  Upper dogleg to have a removable panel to access	1

ID	S	PART NO	DESCRIPTION	QTY
			Head/AC unit for service. Access panel to be custom design with blue block insulation, per Eng design.	
			Compartment "1" handle- 40 7/8" - from bottom of door to center of handle.	
REV		04-06-0476	MD, No Dogleg for Stair chair in Compartment #1	1
REV		04-06-1550	MD, Compartment #1, Shelf, Adjustable, W/Alum Track, First shelf Black polyurethane finish to match comp Install shelf tracks so that bottom of shelf can be 55" from floor, above the O2 viewing window.	1
REV			<b>COMPARTMENT #2 - STREETSIDE FWD WHEELWELL</b>	
REV	XS	04-07-2152	WC, Compartment #2, 50" Aisle, Custom Configuration. (Special Request) Match Previous #554849.  With Double Doors full sweep out Reduce depth of comp "2" for wider aisle space. Enlarge countertop hole for trash can Eng: dogleg may need to be reduced in depth to get larger trash opening. Compartment "2" - 23 7/8" - from bottom of door to center of handle	1
REV		04-07-2630	MD, Compartment #2, Shelf, Fixed, Electrical storage, w/ Divider (10256891) Black polyurethane finish to match comp.  Area to right of divider will be used for waste in A/A and dogleg for recessed suction unit.  Tall trash container #2957 will be mounted on custom adj bracket between dogleg and compt "2" door opening. Install a small adj shelf to support bottom of trash container. Custom layout per reference drawings	1
REV		04-08-2100	MD, Compartment #3, NONE	1
REV			<b>COMPARTMENT #4 - STREETSIDE AFT</b>	
REV	XS	04-09-3249	MD, Compartment #4, Custom (Special Request) Match previous unit # 554849,. With double doors full sweepout NO I/O ACCESS!	1

ID	S	PART NO	DESCRIPTION	QTY
			with (2) angled build outs for SCBA brackets per Eng design of previous units. comp to be approx 58"-59" high interior No venting thru ceiling and wall #3. Only vent to exterior with (2) baffle vents thru lower wall #2 due to hazardous material being stored in this comp. Compartment "4" handle- 40 7/8" - from bottom of door to center of handle	
REV		04-09-3620	MD, Compartment #4, Hooks, (2), For Turnouts, Ferno #559, Installed (2) Rubber coated, Polyurea, blackInstalled in comp "D", per picture on server. Eng: Pre-punch holes if possible.	1
REV		04-09-4556	MD, Compartment #4, Shelf, Fixed, Each Compt 4 placed on top of SCBA build ups Black polyurethane finish to match compt	1
	U	04-09-46SR	Knockdown Bracket, SCBA Mount, Zico KD-UH-6-SF Ref SR # 2230168F Line 13. (10140199)  Must Fit Scott #10009673 carbon wrap 45 min 4500PSI Bottles Mount in Compt "4" (1) centered on angled dogleg across corner of wall #1 and wall #2 (1) centered on angled dogleg across corner of wall #2 and wall #3 Angled buildups will each be approx 28" high.	2
REV			<b>COMPARTMENT #6 - CURBSIDE AFT</b>	
REV	XS	04-11-1098	MD, Compartment #6, Custom (Special Request) Previous (10201503) Same as previous 554840 but not previous units.B2 Comp - Max height x 23.25"W x 19" D Interior Dimensions. Stair chair storage area increased by .5 " from early units, same as 554840.  Full Height DOOR(warning light will be on door) with a wheel bracket for Stryker stair chair  Add pocketed door panel for stair chair requires a raised up floor)	1

ID	S	PART NO	DESCRIPTION	QTY
			Reduce width of comp "6" approx 4.5", area to right of divider. Floor buildup will be approx 13" wide	
			See Photo !!! ref only 337140 thru 439016 had to be fixed/revised.	
			Add buildup or raised cover for recessed switches...	
			Compartment "6" handle- 40 7/8" - from bottom of door to center of handle	
REV		04-11-2097	MD, Compartment #6, Divider, Vertical, Fixed, 3/16" Thick , Each all black polyurethane to match compartments.	3
			(1) from floor to bottom of fixed shelf, approx 4" from wall #3.	
			(1) partial depth, fixed between center divider and wall #1, approx 5" from other full height divider. Notch divider for switches buildup, caulk /seal around bottom edges of divider.	
			(1) fixed and full depth at edge of I/O opening, caulk/ seal around bottom edges of divider.	
REV		04-11-4534	MD, Compartment #6 Shelf, Fixed, Exterior, Each	2
			(1) even with bottom of I/O access	
			(1) in center of I/O access	
REV		04-11-4662	MD, Compartment #6, Flat bar, 2", Backboard Retainer	1
			Black Polyurethane to match compt	
			Flatbar screwed at top of compt "6", between wall #1 and divider, approx 68" from floor to bottom of flatbar.	
REV		04-11-4665	MD, Compartment #6, Recessed Door Panel, Diamond Plate,for Stair Chair	1
			(per eng drawings #384317D Rev C)	
			Recess to be 9.5-10" match previous #554849.	
			comp #6 door panel.	
			Approximately 12.5" of floor near wall #3 to be raised approximately 2.5-3"	

ID	S	PART NO	DESCRIPTION	QTY
			(for 6252 stair chair)	
REV		04-11-4666	MD, Compartment #6, Wheel guide for stair chair Wheel guide is attached to raised Floor for stair chair	1
REV			<b>COMPARTMENT #6.5 - CURBSIDE AFT WHEELWELL</b>	
REV		04-12-0155	WC, Compartment #6.5, Deleted	1
REV			<b>COMPARTMENT #8 - CURBSIDE UPPER FORWARD</b>	
REV		04-14-2200	MD, Compartment #8, Single 1/2 Height Door, Aft of CS Door Forward REF SR # 2230168F, line 21	1
			Full sweep out. Same as 554849 Comp "8" relocated behind the curbside entry door.	
			Single vertically hinged door HINGED REARWARD !!!!! Nader bolt on top to have protective ramp bracket like rear entry door Nader bolts. Handle on comp "8" door to be the same height as the handle on C/S entry door. Delete lip at bottom of RF cab to exterior!!! RF cab divider layout same as 554849 Keep size of drawers at head of S/B the same as PG units. (custom IS/OS access opening)	
	U	04-14-22SR	Shelf, Interior Wood, Fixed REF SR #2230204F, Line 1.	2
REV			<b>INTERIOR TRIM AND FEATURES</b>	
REV		05-01-0105	MD, Interior Cabinets, Duralite Construction, Wood, CN10 compliant NON CN10 Cabinets MUST match previous units , no exceptions, 337140 thru 554840.	1
REV			<b>INTERIOR ADJUSTABLE SHELVES</b>	
REV		05-02-0050	MD, Shelf, Interior, Wood , (1) adjustable, in Cabinet (1) each in cabts "U4" and "U 2" (2) each in cabt "U8"	4
REV		05-02-0054	MD, Shelf Track, Cabinet, #HA24663, CN 10 Upgrade ("C" channel/exterior shelf style track)	4
			<b>**This option may require quantity adjustment**</b>	



ID	S	PART NO	DESCRIPTION	QTY
REV			<b>HEADLINER</b>	
REV		05-06-2860	WC, Headliner, Flat, PVC, Hinged trough cover, 160"+ Eng ref only 554849, these units will have a RECESSED O2 nipple at the head of the cot per Eng design.	1
REV			<b>FLOORING</b>	
REV		05-07-0110	MD, Flooring, Lon Seal "Lon Plate " With approximately 3" roll up both street side and curbside.	1
REV		05-07-0112	MD, Color, Black #163	1
REV		05-07-9897	MD, Floor, Thresholds, .063 Aluminum , Painted w/Black Poly-urea coating	1
REV			<b>Entry Door Grab Handles</b>	
REV		05-10-1533	MD, Entry Door Grab Handles (3), Custom "L" Shape, 1" Stainless Steel For units with Trimark handles.	1
			Stainless Steel Grab Handles	
			ILOS	
REV			<b>Ceiling Grab Rail - Center</b>	
REV		05-10-1930	MD, Ceiling Grab Rail, Overhead,112", 1" Diameter Stainless, Handicap Style	1
REV			<b>GRAB HANDLES</b>	
REV		05-10-7528	MD, Grab Bar, 12" Long, 1.25" Handicap Style, Stainless Steel stainless steel (SAP # 10151728) mounted (1) curb side rear cabinet @ rear entry door (1) street side rear cabinet @ rear entry door (1) on front wall at C/S door	3
REV			<b>IV FLUID HANGERS</b>	
REV		05-11-0015	MD, IV Hook, Perco Snap Hook w/Velcro Strap, Each (1) streetside, on right edge of cabt "U4", per picture on server. (1) curbside, on wall at foot of S/B, per pictures(with dimensions) on server. (1) To be mounted in ceiling beside recessed 02. No strap, just the hook	3
	U		<b>BULKHEAD AREA</b>	

ID	S	PART NO	DESCRIPTION	QTY
	U	05-12-09SR	Cabinet, Bulkhead, Custom Ref SR # 2230204F Line 2. (10201501 Ref previous unit 554849.  Option update 03/15/21 With Sliding Lexan Pass-thru Window, as on #554849. Eng: bulkhead wall to be approx even with C/S door jamb opening. This will allow Zico QR-D-2 Strapless brackets to be partially recessed. Area above, below, and to the left of pass-thru window (below center mounted A/C unit) to be deep enough for circuit board components. All (3) electrical access single doors to be flush mounted with "C" handle & KV-70 locks. Angled cabt door hinged on left. The (2) bulkhead cabt doors to be hinged on right. No hold open cables !!! Recess for suction unit in area to right of cylinder brackets. Knox box down enough to clear hinged trough cover. Opening to allow ease of suction being taken in and out.	1
REV		05-12-1711	MD, Cabinet, A/C, Angled mounting in LF corner Corner style, angled cabinet, ILOS.	1
REV			<b>ACTION WALL AREA #2</b>	
REV		05-13-3093	MD, Cabinet, A/A, 50" Aisle, w/Bio waste, Rounded Corner (SO-SUCT-371440) (10499790)  Same as previous unit 554849.  mica'd recess, per Eng design. Eng: recess may need to be reduced in depth to get larger trash opening. Redesign opening in cabt to allow for customer required 6" x 11" trash access opening !!!!!!!!!!!!!!!  - Move O2 outlets to section above and stretch that panel entire length of action area - Push entire action area wall(area below A/A console) back when the O2 gets moved up Eng: Add "barrier bar", as required. Eng note Height of counter top 28.687" same as customer's last unit	1
REV		05-13-4330	MD, Tray, A/A, 50" Aisle, w/Bio waste, Poured, Black Production to Add holes for Biowaste	1
REV	XS	05-13-4420	MD, AA Upper Cabinets, Custom (Special Request)	1

ID	S	PART NO	DESCRIPTION	QTY
			U2 narrowed up due to relocation of HVAC. Standard U2.5 angled.	
<b>REV</b>			<b>CABINET DOORS</b>	
	U	05-13-4508	MD, Door, U2 Gray Lexan Slider, NOT CN 10 Compliant	1
	U	05-13-4522	MD, Door, U2.5 , Hinged Wood Hinged on Right.	1
			Add J molding to L1 cabinet door opening only, matching 554849.	
<b>REV</b>			<b>Interior Street side #3 - CPR Seat</b>	
REV		05-14-1532	MD, CPR side seat, Fixed Backrest, 25" wide Std.	1
REV		05-14-1534	MD, CPR, Lid, Hinged Flip Up With Trimark Latch	1
REV		05-14-1547	MD, Cabinet U3.5	1
REV		05-14-1577	MD, Cabinet C3.5, deleted For Telemetry Area	1
REV		05-14-1587	MD, Cabinet L3.5, full height, std	1
REV		05-14-4418	MD, "U" Barrier Bar, Padded, 1.5" SS, CPR Seat, Gunmetal Mounted at the front of the CPR side seat vertically in line with the Padded head cushion on the upper AA cabinets.	1
REV		05-14-4554	MD, Telemetry Tray, Poured, Black	1
<b>REV</b>			<b>CABINET DOORS</b>	
REV		05-14-4592	MD, Doors, U3.5 Gray Poly carbonate Slider, CN 10 Compliant	1
REV		05-14-4650	MD, Doors, L3.5, Gray Poly carbonate Slider, CN 10 Compliant	1
<b>REV</b>			<b>STREETSIDE REAR AREA #4</b>	
REV		05-15-5050	MD, Cabinet U4	1
REV		05-15-5113	MD, Cabinet C4, Deleted	1
REV		05-15-5118	MD, Cabinet L4, Deleted	1
<b>REV</b>			<b>CABINET DOORS</b>	
REV		05-15-6115	MD, Doors, U4 Gray Poly carbonate Slider - CN 10 Compliant	1
<b>REV</b>			<b>SQUAD BENCH AREA</b>	
REV		05-16-0046	MD, Squad Bench, No Bio-Waste	1
REV	XS	05-16-0078	MD, Lid, Squad Bench, Custom (Special Request) REF SR 2230168F, Line 24. (10214784) Ref Previous unit 554849	1
REV		05-16-0080	MD, Handle, Trimark, CPR Seat, Std.	1
REV		05-16-0082	MD, Handle, Trimark, Squad Bench, STD	1
REV		05-16-0094	MD, Strut, Gas, 30 LB, Installed	1
REV		05-16-0214	MD, Seatbelt, Assy, (4 Point), Per 4Max, Black, Vert. Mount, (1) Each, CN-8 Above bench Lid mounting (1) for CPR side seat (Delete shop note if not required)	1

ID	S	PART NO	DESCRIPTION	QTY
			(2) for squad Bench	
REV		05-16-0214	MD, Seatbelt, Assy, (4 Point), Per 4Max, Black, Vert. Mount, (1) Each, CN-8 Above bench Lid mounting (1) for CPR side seat (Delete shop note if not required)	2
			(2) for squad Bench	
REV		05-16-0222	MD, Patient Restraint Belts, Squad Bench (3)	1
REV			<b>CURBSIDE REAR</b>	
REV	XS	05-16-9930	MD, Cabinet, Curbside Rear, Custom (Special Request) (10215587) Inside Outside Access Door 3/8 Hinged gray Lexan - On aisle side of curbside rear - Pass through opening 35.75" H x 11.625" W into comp 6, Shall hold closed with Southco Stainless Steel M1 Latch and shall be tethered with a stainless cable held by Perko eyelets	1
	U	05-16-9930	MD, Cabinet, Curbside Rear, Custom, PGC REf SR # 2230204F Line 3.(10154097), same as cust last unit 554849.	1
	U	05-16-99SR	CS Splint, Custom REF SR # 2230168F line 17. (10539501).  Same as previous # 554849 CN10 Compliant cabinets.  Custom Splint Cabinet due to curb side door forward design. Cab U8 - above cabinet at head of squad bench. Inside dimensions to be approx 16" h x 24"w x 9" d, leaving 17.5"h for equipment between cab "U8" and poured tray work surface. Do not install padding on bottom of cab "U8", only very low profile upholstered trim on front edges. Cab to have gray CN10 compliant slider and (2) adjustable shelves Angled area for switches beside cab "U8"(toward rear) Cab U7/ U7.5 - each 6.75"h x 28" w x 9"d, (ID), each with a lift-up 3/8" gray lexan door, each w/(1) special order gas strut. Maintain 43" headroom between squad bench cushion and lower edge of cabinet. ***Must be same height as cabinet above CPR seat***	1

ID	S	PART NO	DESCRIPTION	QTY
	U	05-17-01SR	Sharps drawers, IATS REF SR #2230168F line 15. (10315924)  (1) face of S/B at foot (1) in front of cpr seat Model #8881-676236  Ref previous job # 554849	2
<b>REV</b>			<b>CURBSIDE RIGHT STACK STORAGE #8</b>	
REV	S	05-18-0095	MD, RF ALS, At Head of SB, 1/2 Height, Custom (Special Request) REF SR #221687 line 91(10315925), REF previous #554849  Cabinet at head of squad bench(per Attachment "A") - approx. 39" high x 46.5" wide with (1) drawer underneath work area that pulls out toward aisle. This drawer should approx 27"w interior. (2) drawers below work surface that pull out toward bench. These (2) drawers to be constructed of alum to maximize width & depth. Face of drawers to be mica'd wood. These two drawers to have each have (2) sets of slides. Keep size of drawers at head of S/B the same as customer's last unit 554849! Forward section of cab I/O to Comp 8. Cut out to be approx 29.75"w x 30"h. Caulk around bottom edges of RF cab before installing dridek. Squad bench to be 54.625" long. S/B lid to only overhang face of S/B by approx 1/2", ilos.	1
REV		05-18-3586	MD, Tray, Poured, Black, Head of Squad Bench	1
REV		05-18-5340	MD, RF ALS, L8, Door, Dual Solid Install tether cable on right door to keep from hitting Power Load. Right door to open at least 90 degrees. Left door should NOT have a tether cable.	1
<b>REV</b>			<b>ATTENDANT SEAT</b>	
REV		05-19-6902	MD, Attendant's Seat, EVS 1880,Comfort, Hi-Back Child Safety w/Per4Max	1
REV		05-19-6912	MD, Color, Black, Per4Max Belt, Black	1
REV		05-19-7215	MD, Attendant's Seat Base, EVS CBS Box Style Installed as Thru-Bolt, ILOS, like Power load track, with Nylok nuts. Customer's precise measurements on file in work order folder, for location of seat base !!	1

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>INTERIOR COLORS</b>	
REV		05-20-0030	MD, Mica, Dove Gray (Matte)	1
REV			<b>UPHOLSTERY</b>	
REV		05-20-5916	MD, Upholstery Color, Black Seamless	1
REV		05-20-5970	WC, Backrest Cushion, EVS, Gunmetal, w/ WC Logo, Each	3
	U	05-20-60SR	Cabinet 2.5 Padding REF SR # 2230168F, Line 16. (10214760)	1
			Cabinet U2.5 door to be padded. Seamless BLACK vinyl	
	U	05-20-98SR	Strut, Gas, 7.5", 15lb, (1), for Lexan Flap Upper Cabts Ref SR #2230168F, Line # 5., (10237025)	4
			(4) for lift up lexan doors on cabts "U3", "U3.5", "U7", & "U7.5", (1) on left side of each door.	
			Doors need to open more than 90 degrees.	
	U	05-20-99SR	Cabinet Opening MedVault Mini Ref SR # 2230204F, Line 7. (10819260). Prewire only for delaer installed:	1
			Knox MedVault Mini with Audit trail, lightbar, Ethernet cable back antenna jack, rubber ducky antenna, recessed mount. Mounting location: on side of A/C unit cabt, per drawings. Customer's PS #39-0013-07-85 Unit must be lowered slightly to accommodate hinged trough cover.	
REV			<b>CABINET LATCHES- INTERIOR</b>	
	U	05-21-8196	MD, Handle, C, Pull, Installed, Each (1) on each of the (3) electrical cabt doors	3
	U	05-21-8197	MD, Latch, Plunger Roller, Installed, Not Rated Per CN-10 RF Cabinet drawer facing aisle to keep drawer from coming all the way out	2
	U	05-21-8199	MD, Lock, Key, KV-70, Each (1) on each of the (3) electrical cab doors  ship loose minimum of (5) KV70 keys per unit.	3

ID	S	PART NO	DESCRIPTION	QTY
	U	05-21-81SR	MD, Latch, Southco M1-62-8, Each REF SR# 2230168F Line 4 (SO-LATCH-301040). self latching, flush mount, non locking.  (1) Cabinet U3 (1) Cabinet U3.5 (1) Cabinet U7 (1) Cabinet U7.5 (1) cabinet 6 I/O access door	5
REV		05-21-8213	MD, Latch, Southco M1, 2" S/S, (3/4" door) Non-Locking, CN 10-Rated 10lb (self latching) Flush Mount. Non-Locking  (1) on each drawer facing S/B seat (1) on RF cabt drawer facing aisle (1) on Str/s sharps drawer (1) on C/S sharps drawer	5
REV			<b>GENERAL WIRING</b>	
REV		06-01-0130	WC, Electrical System: Printed Circuit board	1
REV		06-01-0250	WC, Vanner, "E" Spec, PC Board, No LB	1
REV			<b>CAMERAS</b>	
REV		06-06-1245	MD, Camera - WHT Ext B/U, ZORG over Rear Doors for Ford F-series Install one (1)Zorg white IR color camera. Exterior mounted and connected to vehicle's OEM display.	1
REV			<b>COMMUNICATION</b>	
	U	06-06-17SR	Rosco DV 660 Camera system w/ Int.Camera, RoscoLive Per SR#2230418F Remove OEM windshield mounted rear view mirror and install DV660 in its place. Event Button located on front left corner of cab console The 3' cable will need to run to the DV660 and have the splitter attached at the camera. The 16' cable will run to the rear backup camera. Rosco components will include: 4G cellular service. One (1) DV660 Dual XC4 camera One (1) DV441 Event Button, LF corner of CC. One (1) 128GB memory cards One (1) STSC141, rear vision color camera One (1) STSH341, 65.00" camera cable One (1) STSH496, camera splitter cable One (1) DV408 DVXC4   4G LTE Cellular Glass Mount Antenna	1

ID	S	PART NO	DESCRIPTION	QTY
	U	06-06-18SR	Motorola 30' Mobile Radio Cable # HKN6168B REF SR #2230168F Line #2. REF SAP # 1059541.	1
	U	06-06-19SR	Panarama, Shark Fin Antenna GPSD-7-27-24-58 MIMO GPS/GNSS SR 2230418F Shark Fin Antenna. GPSD-7-27-24-58 MIMO GPS/GNSS 2G/3G/4G WLAN ANT, C23F-5M FME(ftd) MPL(ftd) 5m CS23 cable, AFM-835 ANTENNA MOULDED FLEXI- 762-870MHz, C23F-5FP, FME(f)ftd FME(p)ftd 5m CS23 CABLE, DPD-GPS, DUAL POWER DIVIDER GPS 1575MHz FME, C23F-5SMAP FME(ftd) SMA PLUG (ftd) 5m CS23, C29SP-5SJ-CELL CS29 CABLE 5m SMA PLG TO SMA JACK - YEL 2G/3G/4G LABELS, C32SP-5SMARV-WIFI and 5m CS32 CABLE SMA(m) - SMA(m) RP - WIFI LABELS Locate per previous units #554849, PS cab roof rear Run all antenna cables except 800 MHZ to cab console. 800 MHZ terminates behind pass seat in cab	1
	U	06-06-20SR	Motorola 17' Radio Cable #HKN6169B (SAP# 10131986) REF SR #221940R1, Line 7. (1) from radio in cab console to radio base behind passenger seat. #HKN6169B(17')	1
	U	06-06-23SR	Precision Mount Technologies #AS7.P)31.102-PS-1 Mount REF SR #2230168F Line #7  Mount on cab console same as previous units #554849.	1
	U	06-06-24SR	Havis Chargeguard # CG-X REF SR # 2230168F, Line #9.  Same location and wiring as previous unit #554849.  PG wiring diagram in previous units folder.	1
	U	06-06-25SR	Lind Power Supply # PA1555-1654 REF SR # 2230168F, Line #10.  Same location and wiring as previous unit #554849.  PG wiring diagram in previous units folder.	1



ID	S	PART NO	DESCRIPTION	QTY
REV		06-07-6607	MD, Clock, Digital, Display Systems BSA-62425, 12/24 Hr. Per customer supplied Component install Diagram, Previous SR #220752F line 29. Coax to Terminate: behind pass seat in cab	1
	U	06-07-67SR	Hanger, Headset, FireCom #HGR-1 each Ref SR# 2230168F, line 9  #520-0676-00, headset hangers HGR-1 Ship both loose	2
	U	06-07-68SR	Havis Bracket C-EB25XTL-1P Ref SR # 222230168F :Line 27. (10201123)  Havis #C-EB25-XTL-1P 1-piece mounting bracket, 2.5" mounting space, Fits Motorola XTL2500, XTL5000-05 &APX-7500 (1) for C/S cabt radio below !!! C/S aux switch panel !!! (1) in cab console, in cutout of painted aluminum console	2
REV		07-00-0610	MD, Light, in Circuit Board Area, for Electrical Troubleshooting - with integral switch; wired constant hot.	1
REV			<b>POWER SOURCES</b>	
REV		07-01-1010	MD, Power Source, 12 VDC, 20 Amp (+-), Constant Hot Termination:Termination:(1) cab console, (1) A/A console, (1) head of C/S bench at auxiliary panel,1) behind pass seat in cab Tie strap together after labels are applied!	4
REV		07-01-1014	MD, Power Source, 12 VDC, 20 Amp (+-), Ignition Hot  (2) pre-wire coil and tagged in center console, (2) pre-wire coil and tagged behind passenger's seat (2) to Auxiliary switch panel on C/S wall Tie strap together after labels are applied!	6
REV		07-01-1016	MD, Power Source, 12 VDC, 30 Amp (+-), Constant Hot - Constant Hot, to terminate behind the passenger seat - with 6 foot tails (hot and ground).	1

ID	S	PART NO	DESCRIPTION	QTY
REV		07-01-1020	MD, Power Source, 12 VDC, 30 Amp (+-), Ignition Hot Termination: Located in the console w/6' tails, tagged.	1
	U	07-01-10SR	Blue Sea Fuse Block, Capable of 6 circuits up to 125 amps Ref SR # 2230168F, Line 16 (SO-BSFB-363016) Power constant hot Installed in the center console - With 1ea. 30amp power source ran in behind the passenger seat with ground. Blue Sea #5025B ST Blade fuse block, 6-circuits with negative bus and cover	1
<b>REV</b>			<b>VOLTMETER</b>	
REV		07-02-1155	MD, Alarm, Low Voltage, Audio/Visual Light in cab console and Buzzer in cab.	1
REV		07-02-1157	MD, Voltmeter, Glowshift , Digital	1
<b>REV</b>			<b>BATTERY SYSTEM</b>	
REV		07-04-8721	MD, Battery Sw, 5min Timer, F1, Fig 5B, Batt under Hood Activated thru OEM ignition switch timer function upon ignition "off". Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer.  (2) OEM batteries under hood  ONLY Module power is turned on/off. Chassis power is NOT turned off.	1
<b>REV</b>			<b>12VDC OUTLETS</b>	
REV		07-10-1101	MD, Outlet, Power Point Style, (2), A/A - on standard 20-amp ignition hot circuit. ("elect battery switch") Locate action area	1
REV		07-10-1105	MD, Outlet, Power Point Style, Each (2) on the front of console passenger side, constant hot (1) above work surface at head of squad bench - near 110 volt outlet, constant hot	3
	U	07-10-1108	Diode Protection - 30 Amp Service Max REF OLD OPTION 6A-21-1000, Cannot find suggested option # 07-10-1108 in master option list please add.	1
REV		07-10-1109	MD, Power Outlet, Kusssmaul, USB Dual Port, 5VDC, 4.8 Amp, switch panel	2

ID	S	PART NO	DESCRIPTION	QTY
			(1) Located in the cab switch panel per Electrical Engineering, (1) above work surface at head of squad bench - near 12vdc volt outlet	
			ENG ref previous unit # 554849	
<b>REV</b>			<b>FRONT CONSOLE</b>	
REV		08-01-3525	WC, Console, Drivers Switch & Radio, Center, Aluminum, Black, Type1 Ford Black polyurethane coated .090 Aluminum	1
			See below for Optional panels 10.75 x 12.5 x 7" deep storage area at rear	
	U	08-01-37SR	Docking station, Gamber Johnson for Panasonic tough book 40 Lite SR 2230418F computer docking station(s) with power supply and quad RF pass-through for a Panasonic Toughbook 40 Lite laptop computer (computer not included) Installed on center console. There will be one (1) Adjustable Multi-Pattern Tilt with VESA 75 dock mount for each docking station. Docking Station with Power Adapter for Panasonic Toughbook® 40 Lite QPT Item #AS7.P040.102-PS Antenna Pass-Through Quad RF Pass-Through Port Replication 2 x Ethernet (Gbe) 2 x USB 2.0 1 x USB 3.2 2 x Rear USB-C 3.2 1 x Front USB-C 2.0 1 x Serial RS232 1 x Power In 15.0 Vdc 4 x External Antenna Connections (SMA) Features CNC Aluminum construction for rugged reliability Space saving and ergonomic design improves ergonomics and safety Captured key lock with auto-latching mechanism ensures user safety, protection and device security Auto-retracting connector cover to reduce connector damage Integrated genuine Panasonic PCB	1

ID	S	PART NO	DESCRIPTION	QTY
			and connector for trouble free service	
			Rear facing ports with integrated cable tie rail	
			Mounting interface with VESA 75 and PMT Wedge Tilt 1.875" x 1.25" hole patterns	
			Power adapter included	
			Locate Passenger side of cab console.	
			Connect Havis Charge guard and Lind power supply in order to the dock	
REV		08-01-4652	WC, Single Blank Panel	1
REV		08-01-4654	WC, Double Blank Panel	1
REV		08-01-4665	WC, View Safe Switch Panel , Type 1 Only	1
			thirteen (13) Eaton switches, four (4) indicator lights, one (1) dual USB cutout, one (1) voltmeter, and one (1) Whelen 295SLSA1 siren amplifier	
REV		08-02-0006	MD, Module Electrical Panels, Brushed Stainless Steel	1
			brushed stainless steel panels for the Outlet panels, switch panels and other faceplates in the MODULE only.	
REV		08-02-5713	MD, Alarm, Door or Comp Ajar in Gear	1
REV			<b>ATTENDANT CONTROL PANEL</b>	
REV		08-03-0306	WC, Console, A/A, Wood, Angled	1
			NON angled matching previous units ref 554846	
	U	08-03-03SR	Console, S/B, Auxillary Wood	1
			REF SR # 2230168F, line 26. (10201118)	
			Auxiliary Switch Panel Cabinet at the head of the squad bench in addition to action area switch console.	
			(note - switch panel is moved to top of angled area on units after #554849,	
			customer wants to move mounting screws at top of this panel down about 1" to not have to remove upholstery to remove mounting screws. Top center screw would be deleted)	
			A radio gets installed in auxiliary panel on C/S. The Havis plate will be provided but they need to leave about 5" of depth for the radio mount with this custom panel.	
REV		08-04-6103	MD, Switch, 12VDC, (3) Position Rocker, Additional	1
			(1) in cab console for overhead map light, switch should be on the right closest to the passenger	

ID	S	PART NO	DESCRIPTION	QTY
REV		08-04-6105	MD, Switch, 12VDC, Rocker, Amber, Additional Single switch labeled "WARNING LIGHTS" In cab console to turn on ALL warning lights on and off !! NO pri/sec.	1
REV		08-04-6111	MD, Switch, Momentary, Rocker, (1) (1) for checkout light timer. To be recessed w/alum trim around edge of opening.(No ABS !!!) Mount in cabt near right rear entry door, with air suspension dump override switch. Not on entry door!	1
	U	08-04-61SR	Swieth -3 position, For Secondary Angled console Ref SR # 2230168F line 23. (SO-SW1-371417)  Double Switches (Such as Domes Hi/Lo/Off) 1 - for curbside LED Dome Lights - Hi/Lo/Off 1 - for streetside LED Dome Lights - Hi/Lo/Off	2
	U	08-04-62SR	Switch, Momentary, for secondary angled console Ref SR # 2230168F, line 30. (SO-SW2-371417) Single Switches, Momentary 1 - Oxygen On/Off 1 - Exhaust Fan On/Off Suction and Str/s work light will only be switched in Str/s action area.	2
REV			<b>SIREN ELECTRONIC - CONTROL HEADS / AMPS</b>	
REV		09-03-1802	MD, Siren, Whelen, WS-295-SLSA1	1
REV			<b>SIREN SPEAKERS</b>	
REV		09-03-2733	WC, Siren Speakers, Cast SAD3833/SAP3834-23FSD-1, 2023 F-Series w/fog Lts. Thru Front Bumper	1
REV		09-03-3530	MD, Switch, Siren/Horn Thru Horn Ring	1
REV			<b>BACK-UP ALARMS</b>	
REV		09-05-1112	MD, Back-up Alarm, No Cutoff Switch	1
REV		09-40-5177	MD, Cab Headliner Removal Fee, Type 1/3 for dome light installation, antennas. Add trim at rear where liner meets back wall of cab.	1
REV		09-70-5248	MD, Traffic Pre-Empt, Opticom 794H LED Mount emitter on bottom of cool bar, centered. Wire to operate when warning lights are activated and in gear. NO separate switch. Customer will program emitter after delivery.	1

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>WARNING LIGHT FLASHERS</b>	
REV		09-80-2000	MD, Flasher, Vanner 5860GCPE, C/D/E Spec Will flash 75FPM single flash ONLY	1
REV		09-80-5920	MD, Circuit, Neutral Power	1
REV			<b>WARNING LIGHTS</b>	
REV			<b>LED Series - M9 (Flange Included)</b>	
REV		09-95-1723	MD, Light, M9RC, LED, Whelen, Red, Clear Lens, Internal Flash, w/Flange (2) on front of Coolbar.- outboard of center clear. These (2) lights to be sync'd to each other only. alternate flash. Internal flasher: comet flash 75 L/R, (1) phase 1, (1) phase 2. (2) on rear of body to show through rear door windows. These (2) lights to be sync'd to each other and (2) upper corner red M9's. "X" pattern Internal flasher: comet flash 75 L/R, (1) phase 1, (1) phase 2 (2) on rear of body in the corners These (2) lights to be sync'd to each other and (2) red M9's thru upper windows. "X" pattern Internal flasher: comet flash 75 L/R, (1) phase 1, (1) phase 2 (2) on rear upper between amber warning light and rear load light. internal flasher/triple 120 flash left/right, sync together and sync with upper rear amber M9's, phase 2	8
REV		09-95-1725	MD, Light, M9AC, LED, Whelen, Amber, Clear Lens, Internal Flash, w/Flange One rear inboard of outer M9 red warning light each side rear. internal flasher/comet 75 L/R, sync with other amber and upper Red M9's, phase 1	2
REV		09-95-1735	MD,Light, M9D, LED, Whelen,R/C, Clear Lens, Internal Flash, w/Flange (2) each side of module. These (4) lights, Red half to be sync'd simultaneous with rear wheelwell intersection lights. Red portion of lights to be forward. internal flasher/comet flash left/right, phase 1. NOTE: Curb side forward light to be mounted on curb side entry door - high as possible. "Red part of light Forward" (2) Mounted in angled portions of Cool Bar, These (2) lights to be sync'd to each other only. White portion of lights to be outboard. internal flasher/comet flash left/right, phase 1.	6

ID	S	PART NO	DESCRIPTION	QTY
			"Red Forward"	
REV			<b>LED Series - M6 (Flange Separate)</b>	
REV		09-95-3536	MD, Light, Whelen M6, M6RC, Red w/Clear lens, Internal Flashing 2) on front of box, outboard of CoolBar, flush with the top of the M9 series warning lights. These (2) lights to be sync'd to each other only. internal flasher comet flash 75 L/R, phase 1.	2
REV		09-95-3546	MD, Flange, M6 Series, Chrome (1) each	1
REV			<b>WHELEN M2 SERIES LED FLASHING LIGHTS:(Flange Separate)</b>	
REV		09-95-4458	MD, Light, Whelen, M2D, Red/Clear, Lens Clear w/ Flange Whelen M2D LED light with chrome flange: (2) in Grille, w/white downward, sync'd with each other. Mount grille lights , per ref pic, centered in each outboard center trim bar. internal flasher, comet flash, Phase 1 (2) front Intersection, centered over front wheels !!!!!, w/white downward, sync'd with each other internal flasher, comet flash, Phase 1  (2) Whelen M2D LED light with M2GROM Over rear wheels, as low as possible !!! - rear intersection lights White part of light down, on these lights. internal flasher, comet flash, Phase 1 Red portion to sim flash with upper red M9's w/clear downward	6
REV		09-95-4471	MD, Flange, Whelen M2, Chrome, M2FC, Each (2) in Grille (2) front Intersection	4
REV		09-95-4802	MD, Light, Whelen, LINZ6R, LED-Red with chrome flanges  (2) front Intersectors (2) As Grille Lights	4
	U	09-95-SR01	MD, Flange, Whelen M2, Grommet M2GROM , each SR # 2230168F, , line 11.	1

ID	S	PART NO	DESCRIPTION	QTY
			M2GROM for M2 Lights. Provide two one each side over rear wheels as low as possible but at same height as the ones on the chassis over the front wheels.	
<b>REV</b>			<b>EXTERIOR AUTOMOTIVE LIGHTING</b>	
REV		10-01-0056	MD, Taillight Pkg, Whelen, M62 LED Stop/Tail (Clear), Turn Arrow & Max Intensity - Brake- Steady Burn - Turn Arrow – sequential arrow	1
REV		10-01-0121	MD, Turn Signal, Whelen, Amber Arrow, M62T, LED, w/ Flg, Pair Mount outboard of Cool Bar below M6 red warning lights	1
REV		10-01-1309	MD, Flanges, Whelen, (6) Chrome M6 series taillight set	1
<b>REV</b>			<b>ICC/MARKER LIGHTS</b>	
REV		10-01-2177	MD, Light, Clearance, Amber LED, Each On front as clearance lights.	3
REV		10-01-2178	MD, Light, Clearance, Red LED, Each On rear as clearance lights.	3
REV		10-01-2183	MD, Lights, Red, 2", Marker, LED, Pair in bumper	1
	U	10-01-21SR	Marker Light, Whelen 4" in Compt 4 & 6 Doors, ILOS Ref SR # 2230168F line8. Previous units 554849.  #20R00XRR 5MM LED Eng to reference pictures for placement, approx 18" from bottom of door. Flash with turn signal and steady burn with running lights, std.	1
REV		10-01-2250	WC, Corner Cap Lts, Multi, LED, (2) Amber (2) Red w/Flashers - High intensity flashers; thru separate switch	1
<b>REV</b>			<b>FLOOD AND LOAD SYSTEMS</b>	
REV		10-02-2227	MD, Light, Scene Firetech, HiViz, Guardian Jr, 4x6, FT-GSMJR (1) Paint shop: Paint these lights #Maroon #FLNA30177 (1) on rear of module, upper center, ilos load lights. Production: Please install bezel (flange)	6
REV		10-02-2250	MD, Scene Lighting, CS, Activate on Opening of CS Entry Door	1
	U	10-02-22SR	MD, Light Scene, Firetech Hi Viz, Guardian LED Bezel Delete REF SR # 2230168F Line30 (SAP# 10845632) Reference (10547532) Includes #P-GSM-KIT flange kit Order with "Bezel delete" kit FT-GESM-BDKIT	1



ID	S	PART NO	DESCRIPTION	QTY
			Paint shop: Paint these lights #Maroon #FLNA30177	
			Engineering: Ref #554849 for info on this light.	
			(1) on each side of module, center !!!, ilos scene lights.	
			(1) on coolbar, center.(ilo a center white light)	
			w/separate switch in center console	
			Production: Please DO NOT install bezel(flange).	
	U	10-02-23SR	Scene Lighting, Rear Scene Lights Activate on Reverse gear REF SR # 2230168F, Line 12	1
<b>REV</b>			<b>Cab Entry - Lighting</b>	
REV		10-02-8043	MD, Lights, Running Board, Pair, Trucklite 4" LED, Constant Hot	1
			Activated with the cab doors.	
<b>REV</b>			<b>11 - INTERIOR LIGHTING</b>	
REV		11-01-2871	WC, No Lighting Recessed into Trough Cover	1
	U	11-01-28SR	MD lights, Dome , LED Tecniq #E08-LC10-1 Ref SR # 2230168F Line 5. (10139455) (1) in liner above CS steps switched with CS domes.All 7 others in standard dome locations (pre previous unit #554849).	8
			ENG: Right domes high intensity(ilo left domes, low) to activate with module entry doors due to deletion of stepwell light.	
	U	11-01-30SR	Maplight, Techniq 4", #E06-WSOR-1 Silho-X White/red Ref SR # 2230168F line 9. Ref previous 554849. (SO-MAP-329016).	1
			Ign hot.Ignition Hot. In cab headliner above passenger leg areas	
			This light need to be controlled by (1) three-position switch, mounted in the cab console.	
			The center position on the switches would be "off", flip it up, the white light will come on, flip it down, the red light will come on.	
			Passenger switch should be on far right side of console.	
REV		11-01-9032	MD, Timer, Momentary Switch, 15 Minute, Constant Hot BATT TIMER SWITCH HOT ILOS constant hot!	1
			(must have ECX timed battery switch with this option)	
			on bulkhead wall near C/S door so it can be reached from the	

ID	S	PART NO	DESCRIPTION	QTY
			outside, approx 27" from interior floor level. recessed, trimmed with aluminum.(No ABS insert!!) for right domes(high intensity), O2 minder, & O2 light	
<b>REV</b>			<b>SPOTLIGHTS / HANDHELD LIGHTS</b>	
<b>REV</b>			<b>ATTENDANT LIGHT</b>	
	U	11-03-20SR	Lighting, Action Area, LED Hi-Brite Flex, ILOS w/switch Ref SR # 2230168F, line 6. (10167573)	1
			(1) Full length of A/A, recessed along front edge below "U8" cabt, with switch in str/s A/A console.	
			(1) below cabt U2, recessed along front edge, to illuminate countertop, with switch on Aux C/S panel.	
			(1) in Electrical bulkhead cabt w/door magnetic switch for each door, Lights should be on top and both sides of electrical area.	
			LF cabt door hinges on left. (2) bulkhead cabt elect access doors hinge on the right.	
			REF previous unit # 554849	
<b>REV</b>			<b>12 - ELECTRICAL 125 VOLT AC</b>	
<b>REV</b>			<b>SHORELINE INLET</b>	
<b>REV</b>		12-01-9101	MD, Housing, 45 Degree Angled Aluminum for Shoreline (SAP# 10126520) Mounted on driver's side front of module, angled outboard. Eng: height to be approx same as driver's door handle. Painted maroon to match body Angled buildup to have removable panel to allow removal of shoreline inlet. Eng ref customer's last unit 554849.	1
<b>REV</b>		12-01-9114	MD, Shoreline, 20A, Super Auto Eject, Red RED Cover mounted in angled bracket at driver side front of module with removable painted faceplate with add'l slack "SO" code  ANGLED BRACKET TO MATCH PREVIOUS UNIT 554849.	1
<b>REV</b>		12-01-9136	MD, Shoreline Indicator Light, Green LED w/Label wired to operate if the shoreline breaker is set, turns off when tripped  adjacent shoreline inlet	1

ID	S	PART NO	DESCRIPTION	QTY
REV			<b>OUTLETS - 125VAC</b>	
REV		12-02-2110	MD, Outlets, 125 VAC, Duplex, (1) Action Wall, (1) Right Front Cabinet - (1) outlet in action area - (1) outlet on wall at head of squad bench, above work surface	1
REV		12-02-2114	MD, Outlet, 125 VAC, Duplex, Each, State Location: (2) in cabinet "U 2.5" in Ceiling (1) on front of center console, toward passenger side	3
REV		12-02-2120	MD, Outlet, 125VAC, Interior,surface mount, T-Box,w/ S/S Cover, Each (1) in lower comp "8", wall #2, upper center in area to right of divider. Clamp up wire as high as possible against comp ceiling.(keep this outlet despite portable suction bracket being relocated)	1
REV			<b>BLOCKHEATERS</b>	
REV		12-02-4001	Block Heater - With OEM Plug This option does not include a switch. (STANDARD).	1
REV			<b>INVERTER - 125VAC</b>	
REV		12-03-1414	MD, Inverter/Charger, Vanner LifeSine - Mounted on fixed shelf in Compartment "2" MUST BE MOUNTED IN THE SAME PLACE ON ALL OF THE UNITS Inverter to be ignition HOT, no switch  Expanded alum cover to have access opening per pictures of previous units on server  New for 2021 Square D box for inverter, insure its vertically mounted on back wall of cabinet under pass thru window. On last units it was floor mounted on some units and we had to move them at pick up.	1
REV			<b>AUXILIARY ENVIRONMENTAL SYSTEMS</b>	
REV		13-02-0111	MD, Exhaust Fan, Single 12V, in Line Blower	1
U		13-02-01SR	Ventilator, Power Exhaust Ref SR # 2230168F, Line 14. (SO-VENT-329016).Ventilator, Power Exhaust Attwood #1741-4, 230 CFMILOS	1

ID	S	PART NO	DESCRIPTION	QTY
			Str/s upper at rear. (1) Switch in str/s action area. (1) Switch in C/S action area.	
			Access panel to power exhaust in cabt "U4", wall #1.	
	U	13-02-02SR	Vent, Square,. Black IATS Ref SR # 2230168F, line 11. (10256895). Black	1
			cabt "U2.5", angled cabinet wall #2, upper center	
	U	13-02-03SR	Decon Port, AeroClave ADPP-EX System, installed Ref SR # 2230168F, Line 18. (10819260) REF Last unit # 554849	1
			Mount inlet in Compt 4, wall #3, upper right	
			Mount nozzle in rear coleman panel above rear entry doors toward str/s of the recessed clock.	
<b>REV</b>			<b>WHEELED COACH HVAC UNITS</b>	
REV		13-02-5751	MD, Hoses, Heater, No Max, to Rear	1
	U	13-02-57SR	Brass 1/4 Turn Heater Valves Ref SR# 2230168F line 25. (SO-VALVE-329016), add two additional from previous builds, one (1) each side of heater valves.	3
REV		13-02-6028	WC, Air Conditioning Face Plate, Brushed Stainless Steel with WC Logo	1
REV		13-02-6051	MD, Heat/AC Re-Located LF corner HVAC evaporator relocated to street side of front bulkhead adjacent to street side wall.	1
			HVAC to be at 45 degree angle	
REV		13-02-6101	MD, Heat/AC, F1, Combo, Brushless Motor Note: Adding an external condenser is recommended !!	1
REV		13-02-7754	MD, Thermostat, Hoseline Master Control Digital CM5000, Brushless Motor Mount probe in front of evaporator	1
REV		13-02-9110	MD, Carbon Monoxide, Monitor, Surface mounted CONSTANT HOT! Install on str/s A/A switch panel, right side, per picture on server !!!	1
<b>REV</b>			<b>COT MOUNTING PROVISIONS</b>	
REV			<b>Cot Mounts</b>	

ID	S	PART NO	DESCRIPTION	QTY
REV		14-01-1546	MD, Cot Mount, Stryker Power Load, No Wheel Guides, CN 8 Compliant includes constant hot power supply for battery charging.	1
REV		14-01-4028	Center Mount	1
REV			<b>OXYGEN AND AIR SYSTEMS</b>	
REV		14-02-1010	MD, O2 Cylinder Wrench ,Tethered  in oxygen comp.	1
REV		14-02-2252	MD, O2 Cylinder Bracket, Ziamatic, Electric, QR-MV, LH Motor Model # QR-OTSL-U  Zico lift - add labels for "up"/"down" near switch.	1
REV		14-02-3005	MD, Manual, O2 System	1
REV		14-02-3156	MD, O2 Regulator, Preset 50 PSI Ship Loose unless otherwise directed	1
REV	S	14-02-4186	MD, O2 System, Custom (Special Request) Ref SR # 2230168F line 25. (SAP # 10845578). Match previous unit 554849.  Eng Reference only (SO-O2-371440) Ohio style  Electric switch w/bypass in str/s action area, mounted in A/A console ILOS, per Eng design.  (1) oxygen outlet in action area, mounted in A/A console ILOS, per Eng design.  (1) vacuum outlet in suction recess in face of counter wall area(with ADPT-302040 ADAPTER,VACUUM ilos)  (1) O2 outlet at head of squad bench, CS wall per Eng design, see updated ref drawings.  (1) O2 Diss threaded fitting with a O2 nipple recessed in liner at head of cot, CS of wire trough. The unit will have a Flo Tech dial style flow meter in the curb side AA wall just rearward of O2 outlet with a hose ran from flo meter to recessed O2 nipple in liner. The fixture in recess nipple faces forward towards head of cot please.  Eng/Prod note reference information on file in order folder. Must be flow tested and signed off by inspector at each location.	1
REV		14-02-4223	MD, O2 Outlet, Ohio Style Quick Disconnect, Passive, Additional	1

ID	S	PART NO	DESCRIPTION	QTY
			LOCATION: CS wall next to other outlet, match previous unit 554849	
REV		14-02-4920	MD, Lexan Flap, w/Hinge	1
REV			<b>PORTABLE O2 HOLDERS</b>	
REV		14-02-6282	MD, O2 Cylinder Holder, Single, Zico QR-D-2 Strapless, CN 10 Certified on bulkhead, partially recessed, per Eng design.	2
			Per previous # 554849	
REV			<b>SUCTION SYSTEM</b>	
REV		14-03-3000	WC, Suction Outlet and Container located in Action area recess REF previous Unit #554849 for recessed suction in face of AA cabinet	1
REV		14-03-3030	MD, Suction Pump, SSCOR 90206 Locate in recess AA wall.	1
REV		14-03-3045	MD, Suction Port, Hole Only, No Outlet Plate	1
REV		14-03-3070	MD, Suction System, SSCOR 23002 Disposable w/Canister Clip & Regulator NO Ohio style vacuum outlet - plumb hose from SSCOR canister through hole in AA wall panel Meets SAE J3043 Requirements	1
			WHITE HOSE ILOS!	
	U	14-03-31SR	Laerdal Suction Unit, with Mount, Mounted Ref Sr # 2230168F Line 10. SAP # 10137135.  Partially recessed in bulkhead below angled grabhandle. Hardwire to 110vac. Make sure there is enough room to remove unit. includes suction unit and mounting bracket.	1
	U	14-03-32SR	S/S Triple Glove Dispenser, Bowman Medical Model #GS-123 REF SR # 2230168F, line 14. (SO-GLOVE-349040) Mount on curbside door ***below *** "L" handle !! installed with nylock nuts(thru-bolt)	1
REV			<b>MISC MEDICAL</b>	
REV		14-04-1200	MD, Fire Extinguisher, 5# ABC with Surface Mount Bracket., Each HD Amerex Bracket #861H with Amerex 5LB fire extinguisher.	2

ID	S	PART NO	DESCRIPTION	QTY
REV		14-04-5065	MD, Swivel Mount Kit, Technimount, ProSeries 35 for LP 15 #210-00PC15-HD with Standard Base Pro #100-20-UN  Mounted per pictures(with dimensions) on server.  Production: Be sure to save all hardware not used for the customer !!!!!!! please place hardware in a zip lock bag and tie strap it to the mount !!	1
REV			<b>PAINT AND FINISH</b>	
REV		15-00-0200	WC, Wheeled Coach Paint Process	1
REV		15-01-2011	Module Paint, Paint other than OEM, Red or Metallic Note: Must state color with paint code and request a paint spray-out for approval.  NOTE: When requesting a dark module color, REV Group Orlando recommends option 15-01-4010 to paint the roof sheet White. This will reduce heat transfer into the module and increase A/C system efficiency.	1
REV		15-01-5600	Cab Paint - Single Color, Repaint other than OEM, Red or Metallic Note: Must state color with paint code. (Request a paint spray-out for approval id wanted)  Overall cab paint includes Hood.  THE CAB INSERT MUST MATCH THE AREA THAT IT IS INSERTED INTO	1
	U	15-01-59SR	Paint Scene Lights and Load Lights Ref SR# 2230168F, line 2. Labor hours only Maroon #FLNA30177	1
REV			<b>PAINT STRIPING DESIGN</b>	
REV			<b>PINSTRIPE</b>	
REV			<b>GRAPHICS AND LETTERING</b>	
REV	S	15-02-8001	Lettering/Graphics, By Outside Vendor Ref SR # 2230168F, line 1. (10200836) Same as last unit 554849. Customer to provide station numbers, station names, and M numbers (fleet ID numbers). Includes rear chevrons.	1
	U	15-02-81SR	Label, paint Codes and Graphics Info Ref SR # 2230168F, line 1. INCLUDED in Graphics package. (SO-LABEL-349022) Ref customer's last unit 554849 Supplied by 24/Seven Graphics	1

ID	S	PART NO	DESCRIPTION	QTY
			(1) Label to have paint code and graphics/lettering information and list of fluids and refrigerant. Install in comp "2" on alum panel on inside of fwd door of compt 2. . Panel size & placement to match 554849 (per pic on file) Alum panel to be approx the same size as the label.	
REV			<b>DECALS AND NOMENCLATURE</b>	
REV		15-05-0038	WC, Ship Loose, W.C. Standard Items	1
REV		15-05-0055	MD, Spare Tire, OEM only, Ship Loose	1
	U	15-05-01SR	Wheeled Coach Operations Manual, CD Ref SR # 2230168F, line 11. (10132333) - 1 per truck, disc preferred Ref previous unit 554849	1
	U	15-05-02SR	Wheeled Coach As Built Parts Manual Ref SR # 2230168F, line 12 (10155177) - 1 per truck, disc preferred  Ref previous unit 554849.	1
	U	15-05-03SR	Grote 71422 Triangle Kit Ref SR # 2230168F, line 13.(SO-TRI-359054) ship loose.	1
	U	15-05-04SR	Global Industries T9A129100 Wheel Chock Ref SR # 2230168F line 14. (SO-CHOCK-359054). Ship Loose.	1
	U	15-05-05SR	Trucklite 97960-3 Registration Holder REF SR # 2230168F line 15. (SO-HOLDR-349022) ship loose	1
REV		74-09-0099	Indemnification Statement The purchaser agrees to defend, indemnify and hold Rev Ambulance Group harmless from any claims, costs (including actual attorneys' fees), damages and liabilities caused in whole or in part by any alteration or modification of, or changes or additions to the purchased products OR use of product for purposes it was not designed or intended for.	1
REV			<b>End Of Order</b>	
REV			<b>== Factory Ship Loose - EMS Equipment - 1.074 07/28/23 ==</b>	